



TSE 6202 Audio Surveillance GSM Phones



TSE 6202 Audio Surveillance GSM Phones

Technical Data:

Standby/Speaking time :

Net:

Output power : Dimensions : Weight : 45h/2h GSM

GSM Class 2; 900 mHz; 1800mHz 123(L)x50.5(W)x22,5(H)mm

151 gr.

Attachments:

The mobile, that looks from the outside like a normal telephone can simply be programmed by pressing a key. This enables to transmit a conversation so that no one notices it because there are no visual and acoustic activities. During the operation the mobile looks like as if it would be switched off. It also can be used as a usual mobile with all its functions. The audio transmission is of a very high quality because of DSP noise reduction system. Microphone Range: up to 5 m Performance: 900mAh/NiMH Operation Temperature: -10 bis

+55°C





Technical Data:

Standby/Speaking time : 55h/2,5 h
Net : GSM

Output power: GSM Class 2; 900mHz; 1800 mHz

Dimensions: 113(L)x48(W)x22(H)mm

Weight: 133 gr.

Microphone Range: up to 5 m

Performance: 900mAh/NiMH

Operation Temperature: -10 bis +55°C

Attachments:

The mobile, that looks from the outside like a normal telephone can simply be programmed by pressing a key. This enables to transmit a conversation so that no one notices it because there are no visual and acoustic activities. During the operation the mobile looks like as if it would be switched off. It also can be used as a usual mobile with all its functions. The audio transmission is of a very high quality because of DSP noise reduction system.











If you would like further Information about ELAMAN, or would like to discuss a specific requirement or project, please contact us at:

Elaman GmbH German Security Solutions Seitzstr. 23 80538 Munich Germany

> Tel: +49-89-24 20 91 80 Fax: +49-89-24 20 91 81 info@elaman.de www.elaman.de