



TSE 3522  
Room Jammer

95  
66  
28  
4  
5  
43  
69  
78  
6  
4  
6  
03  
74  
47  
1  
1  
7  
7  
8  
18  
0  
27  
35  
5  
1  
5  
3  
7  
36  
57  
6  
61  
2  
32  
1  
28  
5  
48  
19  
1  
61  
85  
97  
10  
5  
6  
2  
1  
7  
9  
0  
7  
4  
8  
0  
9  
7  
1  
3  
5  
8  
4  
2  
8  
6  
4  
1  
7  
9  
1  
5  
4  
1  
9  
8  
5  
6  
1  
5  
7  
3  
8  
1  
4  
7  
0  
7  
9  
7

## TSE 3522 Room Jammer

### TSE 3522 TECHNICAL MANUAL

The TSE 3522 Jammer is based on Gamma's long standing technological leadership and its proven jamming technology. Gamma's widely used product base attests to Gamma's determination to provide high end, quality products to customers around the world.

### SPECIFICATIONS

#### FREQUENCY RANGE

GSM double Band  
890-1920 MHz

#### OUTPUT-POWER

890-970 MHz: 1.5W  
1820-1920 MHz: 1.5W

#### MODULATION

Special-Digital Sweep

#### INPUT DC:

24-26V automatic/1.3A  
(DC-Box 95-240VCA)

#### MAXIMUM CONTROL PANEL (JAMMER DISTANCE)

900Mhz: 14-20m  
1800MHz 12-20m  
(max. 400 sqm in rooms)

#### 2 ANTENNAS/SMA CONNECTOR

**DIMENSIONS:** 110 x 170 x 64 mm

**WEIGHT:** 550 g





If you would like further Information about ELAMAN,  
or would like to discuss a specific requirement or project, please contact us at:

**Elaman GmbH**  
**German Security Solutions**  
**Seitzstr. 23**  
**80538 Munich**  
**Germany**

**Tel: +49-89-24 20 91 80**  
**Fax: +49-89-24 20 91 81**  
**info@elaman.de**  
**www.elaman.de**