



**Video Receiver
VRX-5800/32**
(with audio channel)

Miniature Transceiver Systems -Video - 130



Video Receiver - VRX 5800/32 (with audio channel)

Description

When combining the compact high grade video receiver VRX 5800/32 with the miniature video transmitter VTX 5800/500 (Model No.: 130 100 0054), it will constitute a powerful video link. 32 different preprogrammed channels can be selected via a pushbutton switch. The VRX 5800/32 is equipped with a standard audio and video output and has one antenna input. Programming can be carried out with the use of an on-screen display.

Technical Data

Frequency Range	5.650 – 5.950 GHz
Video Bandwidth	30 Hz to 5 MHz
Video Signal Output	CCTV or CTV signal, 1 V _{pp} into 75 Ω
Audio Bandwidth	15 Hz to 15 kHz
Audio Signal Output	500 mV into < 1 kΩ
Power Supply	7 - 30 V DC
Power Consumption	approx. 250 mA (at 12 V)
Dimensions	105 x 48 x 100 mm
Antenna Connection	1 x SMA, 50 Ω

Scope of Delivery: VRX 5800/32,
Plug-in PSU,
Omni Directional antenna – SMA,
Operating instructions.
Transport box



If you would like further Information about ELAMAN,
or would like to discuss a specific requirement or project, please contact us at:

Elaman GmbH
German Security Solutions
Seitzstr. 23
80538 Munich
Germany

Tel: +49-89-24 20 91 80
Fax: +49-89-24 20 91 81
info@elaman.de
www.elaman.de